



12V Bleiakku 12V 2,9Ah 99x59x79mm



block pricing

Menge

bis 3

ab 4

ab 8

Stückpreis

19,90 €*
19,40 €*
18,90 €*

* Preise inkl. gesetzlicher MwSt. zzgl. Versandkosten

Marke: Multipower

Bestell-Nr.: 33-175-00035

Bleiakku 12V 2,9Ah

12V 2,9Ah Bleiakku

Wiederaufladbar, wartungsfrei und verschlossen durch Ventilregulierung. Niedrige Selbstentladung, lange Gebrauchsdauer, einfache Ladung, kein Gefahrgut

Technische Daten:

- Spannung: 12 Volt
- Leistung: 2,9Ah = 2900mAh Kapazität
- Kontakte: 2 x 4,8mm Flachstecker (Faston 187)
- **Lageunabhängig zu betreiben auslaufsicher durch GEL Technik**
- Wiederaufladbar
- wartungsfrei und verschlossen durch Ventilregulierung
- niedrige Selbstentladung
- lange Gebrauchsdauer
- einfache Ladung
- kein Gefahrgut
-
- Betriebstemperatur -15 °C - 40 °C
-
- Abmessungen
- Höhe: 99mm mit Kontakten: 107mm
-
- Breite: 59mm
-
- Tiefe: 79mm
- Gewicht: 1,2kg

Weitere Technische Daten des Akkus

- Float Charging Voltage 13.50 to 13.80V
- max Charging Voltage 14.4 to 15.0V
- Internal Resistance (at 1KHz) Approx. 30 mOhm
- Maximum Charging Current \leq 0.87A
- Maximum Discharge Current for 5 seconds: 43.5A
- Nominal Capacity
- 20 hour rate (0.145A to 10.50V) 2.9Ah
- 10 hour rate (0.276A to 10.50V) 2.755Ah
- 5 hour rate (0.493A to 10.20V) 2.465Ah
- 1 C (2.9A to 9.60V) 1.643Ah
- 3 C (8.7A to 9.60V) 1.16Ah
- Industrie Standard Type
- Case Material ABS (UL94 HB flame retardant case / cover)
- RECHARGEABLE SEALED LEAD ACID BATTERY